





Drop-Forged Alloy-Steel

V8T214 14-Pc SAE Angle


• 30° & 60° Angles Allow Use in 4 Different Positions • Inc: ³/8", ⁷/16", ¹/2", ⁹/16", ⁵/8", ¹¹/16", ³/4", ¹³/16", ⁷/8", ¹⁵/16", 1, 1¹/16", 1¹/8" & 1¹/4"

SRP **\$96.07**

USER \$141.55

V8T7814

SAE Crowfoot




 Fully Polished • Includes: 1¹/₁₆", 1¹/₈", 1³/₁₆", 1¹/₄", 1⁵/₁₆", 13/8", 17/16", 11/2", 15/8", 111/16", 13/4", 13/16", 17/8" & 2"

SRP \$132.25 USER \$192.81

V8T8109

9-Pc Metric Super-Thin

Includes: 8mm x 9mm, 10mm x 11mm, 12мм х 13мм, 14мм х 15мм, 16мм х 17мм. 18мм х 19мм. 20мм х 21мм. 24мм х 27мм, 30мм х 32мм



V8T9215 15-Pc Jumbo SAE Service



 Use in Confined Spaces Drop-Forged Alloy Steel

• Includes: ³/4", ¹³/16["], ⁷/8", ¹⁵/16["], 1", 1¹/16["], 1¹/8["], 1³/16["], 1¹/4["], 1⁵/16["], 1³/8["], 1⁷/16["], 1¹/2", 1⁹/16", 1⁵/8"

SRP **\$171.21** USER \$252.50



USER \$24.33

SRP \$16.51

SP40260 Universal Spring Compressor 2-Pc Internally Threaded Spring Compressor is a Great Option for MacPherson Strut, Coilover & other Accessible Springs • 1" - 11" of Travel & 2645 lbf Max Working Load with **3x Safety Factor** • Vinyl Coated Ends, Safety Jaw & Ball Bearing Load Surface • Use of both Hooks per Spring is Required SRP \$220.91 USER \$286.19 SP86370 GM Van Cas/Cam Plate • Front Adjustment Range: Camber/Caster +/- 1.50°

- Installation Time: 0.3 Hr/Side Required: 1 Kit per Wheel
- Designed to be Adjusted with a ³/8" Drive Breaker Bar

USER \$7.94 SRP **\$6.12**



1/4° Rear Half Shim for Chrysler

Adjusts Camber or Toe

SRP **\$20.12**

SP77350 Ford Super Duty Tie Rod Tool

• 8 Position Tool allows 360° Rotation without Removing Adjuster Block from Sleeve

> USER \$118.61 SRP **\$91.56**

SP88810 W-Body Clamp

LTD QTY



• High Grade Carbon Steel, 2 per Package

SRP **\$11.93** USER \$15.45