

Hose Repair Kit,

1/4" - 5/16"

- Hose Barbed End is 5/16"; Threaded End is 12MM
- Can be used with either .250" or .3125" Hose
- Works well to Repair **JIM1087** Leakdown Tester, or 12MM Spark Plug Threads Found on all Twin Cams, or XL 1986 & later as well as Screamin' Eagle EVO BT Heads

SRP **\$51.58** USER \$59.80



JIM1772

7-IN-1 Torx® Key Set

- Keys are Heat Treated Alloy Steel
- Folded Length is 41/4"
- Includes Sizes: T-10, T-15, T-20, T-25, T-27, T-30 & T-40

SRP **S50.44** USER \$65.10

JIM38515-91 **Nut for Clutch Spring Compressor Tool**

- Use on ALL Sportster® 1991 Present Use on ALL Buell® 1991 - 2009 Includes ALL Buell® Blast, except 1125R
- Must be used with JIM38515-90 Main Body
- Includes: Nut, Washer, Retaining Ring & Instruction Sheet

SRP **\$66.14** USER \$76.20

JIM753


Mighty Bite Flywheel Lock

- Use on ALL Twin Cam Motors
- To Lock Crankshaft when Servicing
- Just Take Out the Crank Position Sensor & Install "Mighty Bite" into Case
- Tool has an Added O-Ring to Prevent Oil Seepage

SRP **\$45.61** USER \$51.65



Fork Leg & **Tube Holder Tool**



- Use to Hold Fork Legs & Tubes for easy Hands Free Servicing or Rebuilding
- Mounts in Vise to Hold Fork Firmly during Repair without causing Damage to the Fork Assembly
- Will not Scratch Finishes

SRP **\$157.28** USER \$183.20



JIM970 3rd Hand Axle Locker Tool

• Use on all 2002 and later FL

Have you Noticed as you are

Torquing Down the Axle Nut after you set the Proper Belt Tension, (Deflection) the Welded Axle Nut will move to the Low Side of Adjuster Cam? This Movement will allow the Belt to lose Adjustment. Place this Tool over the Welded Nut on Left Side with the Neck Portion of the Tool Resting over the Swing Arm.

USER \$85.65

SRP **\$78.16**





SI16504 Paint Pen. Red 12/box

- Marks on Metal, Plastic, Glass. Wood, etc Withstand Temperatures in
- Excess of -50°F 150°F Precision Valve Accurately Meters Flow

MADE IN USA

USER \$7.73 SRP **\$7.12**/ea



250 Gas Welding & Cutting

Kit Medium Duty

- Cuts up to 5", Welds up to 1.25" Steel with Optional Larger Tips
- Includes: Acetylene & Oxygen Regulators, Torch Handle & Cutting Attachment, Cutting Tip (Cuts up to 1/2"), Welding Nozzle (up to 1/8"), 2.5' of 3/16" Twin "T" Grade Hose with CGA "B" Fittings, Glasses, Spark Lighter & Check Valves

USER \$596.24

SRP \$588.40

2" Mini **Grinding Discs**

SI13083

Assortment with Type "R" Twist-to-Lock Holder with 1/4" Mandrel, Green Zirconia



• 25.000 RPM

• 6 Pack: (2) 50 Grit, (2) 36 Grit, (2) 24 Grit

USER \$28.61

SRP **\$26.35**

Surface Conditioning Prep Discs,

Twist-to-Lock 2<u>5/Package</u>

SI13020 (632TB)

3" Star-Brite Discs, Medium/Maroon

USER \$58.40 SRP **\$36.11**

SI13062

2" Star-Brite Discs, Coarse/Brown

USER \$40.56 SRP **\$20.72**

Cut-Off Wheels

MADE IN USA 10/Pack

5123 2" x 1/8" x 3/8"

- Aluminum Oxide, Reinforced with Fiberglass
- 54 Grit 45,000 RPM

USER \$29.24 SRP **\$26.93**

SI12017 Lead Free Wire Solder

95/5% Tin Antimony Alloy; 1/8" 1/4 LB SRP **\$21.81** USER \$23.67



